





VTF SERIES

Traditional Outdoor Fixed LED screen





CONTENTS

- 01** Product Overview
- 02** Scope of Applications
- 03** Product Features
- 04** Product Specifications





Product Overview

Traditional cabinets outdoor applications





Traditional Classical Design Solution for any outdoor conditions



Multiformit

Iron & Die casting Cabinet optional



Creative Shape

Creative shape for options



Full Range

From 2.8mm to 10mm




Maintenance

Front & Rear maintenance is available





Product Detailed Vision





Scope of Applications

Wide applications, outdoor fixed installations





Scope of Applications

Durable and stable Show excellent pictures

Commercial street, Shopping mall, Office building,
Train station, Pedestrian street, Central park, street
cross etc.






Product Features

Design with economical alive






Appearance COMPACT APPEARANCE





Die-Casting Aluminum Optional





Performance

Large viewing-angle, high brightness

- Horizontal view angle 160° / Vertical view angle 140° ;
- High Brightness reached to 6500nits; , which can fit more outdoor advertisements applications, outdoor stadiums and even in bright sunlight environment.





Front or Rear maintenance


Front/Rear maintenance option

The cabinet support front maintenance. Modularization design is convenient for installation and maintenance, which can fit customer demands better.





Standard weight reduce



Only for Aluminum cabinet

- Cabinet size: 1000*1000mm;
- Standard cabinet material: Steel
- EMC cabinet material: Aluminum. Compared with traditional steel cabinet it's 20Kg lighter. When installed on column or on the wall it can decrease the weight to steel structure and save more steel structure material. Greatly saving the cost of transport and labor!





Perfect Heat Dissipation



There are 4 pcs fans, which can improve the heat dissipation efficiently to ensure good and stable play performance.



Folding support handles



➤ Folding support handles , simple and easy, which are convenient for storage and transportation.



Product Specifications

Strong, Stable and High Brightness





Specification

VTF models

| Pixel pitch | 2.8mm | 3.6mm | 5mm | 6mm | 8mm | 10mm |
|-------------------------|---|-----------|-----------|-----------|-----------|-----------|
| LED configuration | SMD1415 | SMD1921 | SMD2727 | SMD2727 | SMD2727 | SMD2727 |
| Brightness | 5000 nits | 5500 nits | 5500 nits | 6000nits | 6000nits | 6000nits |
| Viewing angle | 150°/ 140° | | | | | |
| Scan mode | 1/14 | 1/12 | 1/8 | 1/8 | 1/2 | 1/2 |
| Refresh rate | 1920 | 1920 | 1920 | 1920 | 1920 | 1920 |
| Processing | 14 bits | 14 bits | 14 bits | 14 bits | 14 bits | 14 bits |
| Module size | 160x160mm | 160x160mm | 320x160mm | 192x192mm | 320x160mm | 320x160mm |
| Panel size | 960mm x 960mm x 125mm (W x H x D) | | | | | |
| Panel weight | 42kg/pcs | | | | | |
| Input voltage | AC100~240V 50/60 HZ | | | | | |
| Power consumption (Avg) | 240W/sqm | | | | | |
| Power consumption (Max) | 720W/sqm | | | | | |
| Working temperature | -40°C~60°C | | | | | |
| IP rating | IP65/IP54 | | | | | |
| Life span | 100,000 hrs | | | | | |
| Warranty | 24 months full warranty + 12 month free maintenance | | | | | |

